

**AMENDMENTS TO THE CLAIMS:**

Please replace the claims with the claims provided in the listing below wherein status, amendments, additions and cancellations are indicated.

1. (Currently Amended) A car seat, comprising[[,]]  
~~in a front part inside a seat cushion;~~ a catching part being disposed in a front  
part inside a seat cushion, said catching part extending in a widthwise direction of the  
seat cushion and arranged [[such]] so as to be movable up and down[[,]]; and  
an inertial force application ~~means~~ mechanism that is activated by an inertial  
force at [[the]] a time of rapid deceleration operable to move the catching part  
upward.
2. (Currently Amended) The car seat according to claim 1, wherein:  
the catching part is supported by a reinforcing member inside the seat cushion  
such that it is swingable up and down around a pivot shaft on a rear side of a vehicle  
relative to the pivot shaft; and  
the inertial force application [[means]] mechanism includes an inertial mass  
part arranged forward of the catching part and the pivot shaft and above the pivot  
shaft, and a coupling part for connecting the inertial mass part and the catching part.
3. (Currently Amended) The car seat according to claim 1 or 2, wherein:

the catching part is coupled to a support spring member that supports a lower side of the seat cushion, using an elastic member having a smaller maximum tension force than the inertial force that acts during the rapid deceleration.

4. (Currently Amended) The car seat according to claim 1, further comprising a locking [[means]] mechanism operable for stopping downward movement of the catching part that is moved upward by the inertial force during the rapid deceleration.

5. (Currently Amended) A [[The]] car seat according to claim 4, wherein a catching part being disposed in a front part inside a seat cushion, said catching part extending in a widthwise direction of the seat cushion and arranged so as to be movable up and down;

inertial force application means for moving the catching part upward when activated by an inertial force at a time of rapid deceleration; and

locking means for stopping downward movement of the catching part that is moved upward by the inertial force during said rapid deceleration, the locking means comprises: including a locking member that is always kept in contact with a support member with biasing means, the support member coupling and supporting the catching part and the inertial mass part with each other[[:]] and further including an

engagement portion formed to the support member to be engaged with the locking member when the catching part moves more than a predetermined distance.

6. (Currently amended) The car seat according to claim 5, wherein:  
the support member has two extensions from the pivot shaft toward the catching part side and the inertial mass part side;  
the latter is substantially J-shaped when viewed from one side of the vehicle;  
the locking member is arranged on ~~[[the]]~~ a front side of the vehicle relative to the support member; and  
a curved portion at the front end of the letter J of the support member forms an engagement portion to be engaged with the locking member.

7. (New) The car seat according to claim 4, wherein the locking mechanism includes:  
a locking member that is maintained in biased contact with a support member, the support member coupling and supporting the catching part and the inertial mass part with each other; and  
an engagement portion formed to the support member to be engaged with the locking member when the catching part moves more than a predetermined distance.

8. (New) The car seat according to claim 7, wherein:

the support member has two extensions from the pivot shaft toward the catching part side and the inertial mass part side;

a one of the extensions toward the inertial mass part side is substantially in a form of a letter J when viewed from one side of the vehicle;

the locking member is arranged on a front side of the vehicle relative to the support member; and

a curved portion at a front end of the letter J of the one of the extensions of the support member forms the engagement portion to be engaged with the locking member.

9. (New) The car seat according to claim 4, wherein the locking mechanism includes:

a support member coupling the catching part and the inertial mass part with each other, said support including gear teeth carried thereon; and

a pendular member having other gear teeth for engaging said gear teeth of said support member when brought out of a normally disengaged state therewith by the rapid deceleration against a bias which operates to maintain the normally disengaged state in the absence of said rapid deceleration, engagement of said gear teeth and said other gear teeth preventing said downward movement of the catching part.

10. (New) The car seat according to claim 1, wherein said catching part includes a pipe material having a circular cross-section.

11. (New) The car seat according to claim 1, wherein said catching part includes a material having a triangular cross-section oriented such that a flat side of said triangular cross-section is parallel to an upper surface of the seat cushion in normal conditions.